



| REV. | REVISIONS  | REC. | REV. | REVISIONS | REC. |
|------|--|------|------|-----------|------|
| 1    | CANCEL (M),(R),(C1),(I),(P),(O); CHANGE (C3)->(C1); ADD (I). |      |      |           |      |
|      |  |      |      |           |      |
|      |  |      |      |           |      |

|   |             |                   |                       |                               |                                |
|---|-------------|-------------------|-----------------------|-------------------------------|--------------------------------|
| DRAWN & DRAFTED BY<br>WU FANG   | TOLERANCES  |                   | ANGLE:<br>±1°         | TITLE:<br>T-H BOBBIN PQ-35X35 |                                |
|   | 0<L≤4 ±0.1  | pin pitch<br>±0.2 | UNIT:<br>MM           | BOBBIN MATERIAL:<br>PET FR530 | UL REC.<br>UL 94V-0            |
| CHECKED & APPROVED BY<br>TIAN BAI SEN   | 4<L≤16 ±0.2 |                   | ORIGIN:<br>SZ         | PIN MATERIAL:<br>CP WIRE      | PIN TENSION LOAD:<br>2.0KG MIN |
| <b>PIN SHINE INDUSTRIAL CO., LTD.</b><br>TEL:886-2-22990545      FAX:886-2-22990546 |             |                   | DATE:<br>APR.10 '2003 | DRAWING NO.<br>P-3529         | REV.<br>1                      |